


	Sales document	Doc.: 9003493
		Rev.: 04
Octave sound power levels / Oktav-Schalleistungspegel		Page: 1



Language: English  
Department: Engineering / TAP

Author  30-04-2024	Reviewer  07-05-2024	Approver  07-05-2024
---	---	---



# Octave sound power levels / Oktav-Schalleistungspegel

Nordex N175/6.X

© Nordex Energy SE & Co. KG, Langenhorner Chaussee 600, D-22419 Hamburg, Germany

All rights reserved. Observe protection notice ISO 16016.

Alle Rechte vorbehalten. Schutzvermerk ISO 16016 beachten.

**Nordex N175/6.X – Operating modes and hub heights / Betriebsweisen und Nabenhöhen**

operating mode / Betriebsweise	rated power / Nennleistung [kW]	available hub heights / verfügbare Nabenhöhen [m]		
		112		179
Mode 0	6800	●		●
Mode 1	6525	●		●
Mode 2	6220	●		●
Mode 3	6070	●		●
Mode 4	5940	●		●
Mode 5	5800	●		●
Mode 6	5670	○		○
Mode 7	5560	○		○
Mode 8	5030	○		○
Mode 9	4920	○		○
Mode 10	4820	●		●
Mode 11	4680	●		●
Mode 12	4460	●		●
Mode 13	4260	●		●
Mode 14	4050	●		●
Mode 15	3860	●		●
Mode 16	3670	●		●

- mode available / Betriebsweise verfügbar
- mode on request / Betriebsweise auf Anfrage
- mode not available / Betriebsweise nicht verfügbar

Abbreviations / Abkürzungen:

STE ... Serrated Trailing Edge / Serrations

**Octave sound power levels / Oktav-Schalleistungspegel**  
**Nordex N175/6.X with and without / mit und ohne serrated trailing edge**

Basis / Grundlagen:

The expected octave sound power levels of the Nordex N175/6.X are to be determined on basis of aerodynamical calculations and expected sound power levels. These values are valid for 112 m, [REDACTED] and 179 m (see available hub heights on pg. 2).

The expected octave sound power levels are only for information and will not be warranted.

Die erwarteten Oktav-Schalleistungspegel der Nordex N175/6.X werden auf der Basis aerodynamischer Berechnungen und der erwarteten Gesamt-Schalleistungspegel ermittelt. Diese Werte sind gültig für die Nabenhöhen 112 m, [REDACTED] und 179 m (siehe verfügbare Nabenhöhen auf S. 2).

Die erwarteten Oktav-Schalleistungspegel dienen nur der Information und werden nicht gewährleistet.

## Nordex N175/6.X without STE / ohne STE

octave sound power levels / Oktav-Schallleistungspegel in dB(A)									
operation mode / Betriebsweise	octave band mid frequency / Oktavband-Mittenfrequenz								
	63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz	Total
Mode 0	89.7	96.5	100.7	102.2	104.1	102.3	91.1	73.4	108.9
Mode 1	89.3	96.1	100.3	101.8	103.7	101.9	90.7	73.0	108.5
Mode 2	88.8	95.6	99.8	101.3	103.2	101.4	90.2	72.5	108.0
Mode 3	88.3	95.1	99.3	100.8	102.7	100.9	89.7	72.0	107.5
Mode 4	87.8	94.6	98.8	100.3	102.2	100.4	89.2	71.5	107.0
Mode 5	87.3	94.1	98.3	99.8	101.7	99.9	88.7	71.0	106.5
Mode 6	86.8	93.6	97.8	99.3	101.2	99.4	88.2	70.5	106.0
Mode 7	86.4	93.2	97.4	98.9	100.8	99.0	87.8	70.1	105.6
Mode 8	84.2	91.0	95.2	96.7	98.6	96.8	85.6	67.9	103.4
Mode 9	83.8	90.6	94.8	96.3	98.2	96.4	85.2	67.5	103.0
Mode 10	83.3	90.1	94.3	95.8	97.7	95.9	84.7	67.0	102.5
Mode 11	82.8	89.6	93.8	95.3	97.2	95.4	84.2	66.5	102.0
Mode 12	82.3	89.1	93.3	94.8	96.7	94.9	83.7	66.0	101.5
Mode 13	81.8	88.6	92.8	94.3	96.2	94.4	83.2	65.5	101.0
Mode 14	81.3	88.1	92.3	93.8	95.7	93.9	82.7	65.0	100.5
Mode 15	80.8	87.6	91.8	93.3	95.2	93.4	82.2	64.5	100.0
Mode 16	80.2	87.0	91.2	92.7	94.6	92.8	81.6	63.9	99.4

## Nordex N175/6.X with STE / mit STE

octave sound power levels / Oktav-Schallleistungspegel in dB(A)									
operation mode / Betriebsweise	octave band mid frequency / Oktavband-Mittenfrequenz								
	63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz	Total
Mode 0	89.7	96.5	99.9	100.4	101.3	99.2	89.9	73.4	106.9
Mode 1	89.3	96.1	99.5	100.0	100.9	98.8	89.5	73.0	106.5
Mode 2	88.8	95.6	99.0	99.5	100.4	98.3	89.0	72.5	106.0
Mode 3	88.3	95.1	98.5	99.0	99.9	97.8	88.5	72.0	105.5
Mode 4	87.8	94.6	98.0	98.5	99.4	97.3	88.0	71.5	105.0
Mode 5	87.3	94.1	97.5	98.0	98.9	96.8	87.5	71.0	104.5
Mode 6	86.8	93.6	97.0	97.5	98.4	96.3	87.0	70.5	104.0
Mode 7	86.4	93.2	96.6	97.1	98.0	95.9	86.6	70.1	103.6
Mode 8	84.2	91.0	94.4	94.9	95.8	93.7	84.4	67.9	101.4
Mode 9	83.8	90.6	94.0	94.5	95.4	93.3	84.0	67.5	101.0
Mode 10	83.3	90.1	93.5	94.0	94.9	92.8	83.5	67.0	100.5
Mode 11	82.8	89.6	93.0	93.5	94.4	92.3	83.0	66.5	100.0
Mode 12	82.3	89.1	92.5	93.0	93.9	91.8	82.5	66.0	99.5
Mode 13	81.8	88.6	92.0	92.5	93.4	91.3	82.0	65.5	99.0
Mode 14	81.3	88.1	91.5	92.0	92.9	90.8	81.5	65.0	98.5
Mode 15	80.8	87.6	91.0	91.5	92.4	90.3	81.0	64.5	98.0
Mode 16	80.2	87.0	90.4	90.9	91.8	89.7	80.4	63.9	97.4